

## ROOF JACK / T-TOPS

**PRODUCT:**

T-Tops are designed for pitched roof installation. T-Tops allows air movement and combustion release in combustion with attic cavity ventilation systems. T-Tops are available in Zincalume, Galvanized and Soft Aluminum for "S" Tile roofs. All T-tops have a Die Formed Base with a 1/2" lip for no chance of a leak.

T-tops are available with 1/4" screen and end caps on request.

**FLANGE:**

Galvanized T-Tops are available in FHA base or Standard Base  
Aluminum T-Tops are only available is FHA base.

**MATERIAL:**

ASTM A653 Galvanized Steel  
ASTM B370 Sheet Copper 16oz  
ASTM 3003 H14 Aluminum

**INSTALLATION:**

Vents can be nailed or riveted using conventional hand or power tools. Flashings shall be properly fastened to the substrate by means of wood or metal screws.

Recommended use of this product is for exhaust of warm dry air. This product is not intended for venting grease or liquid.



<b>T-TOP CHART</b>				
<b>Part #</b>	<b>Diam.</b>	<b>STD Flange</b>	<b>FHA Flange</b>	<b>Material</b>
T4GS	4"	4"	---	GALV
TTFB4GS	4"	---	6"	GALV
T7SG	7"	4"	---	GALV
TTFB7GS	7"	---	6"	GALV
T4AS	4"	---	6"	ALUM
T7AS	4"	---	6"	ALUM