PRODUCT DATA SHEET

T-TOPS

Roof Jacks

Overview

T-Tops provide ventilation for pitched roofs as part of an attic ventilation system. Each has a die-formed base with a 1/2-inch lip. Zincalume, galvanized steel and soft aluminum options are available, including soft aluminum for S-tile roofs.

1/4-inch screen and end caps are available on request.



Base Options

Galvanized T-Tops are available with standard or FHA bases. Aluminum T-Tops are available with an FHA base.

Materials

ASTM A653 galvanized steel
ASTM B370 sheet copper - 16 oz.
3003-H14 aluminum

Installation and Use

Fasten vents and flashing securely to the substrate using appropriate nails, rivets, or wood or metal screws and conventional hand or power tools.

Recommended for exhaust of warm, dry air. **Not intended for venting grease or liquid.**

Sizes and Bases

Part No.	Dia.	STD	FHA	Material
T4GS	4 in.	4 in.	-	Galv.
TTFB4GS	4 in.	-	6 in.	Galv.
T7SG	7 in.	4 in.	-	Galv.
TTFB7GS	7 in.	-	6 in.	Galv.
T4AS	4 in.	-	6 in.	Alum.
T7AS	7 in.	-	6 in.	Alum.

STD and FHA columns show flange widths.
Galv. = galvanized steel. Alum. = aluminum.

323-263-9383 | 1353 Philadelphia St. #101 | Pomona, CA 91766
sales@m5steel.com
m5steel.com